





CLASSROOM MODELS

	ENTRY LEVEL			FULL FEATURED	WIDESCREEN	LOW MAINTENANCE
Note: Photos are not sized to scale.						
MODEL	LC-XBL20 / 25	LC-XBL30	EIP-2600	LC-XB100A / 200	LC-WB100	LC-XS25 / 31
KEY FEATURES	Operates as quiet as 29 dBA; Network monitoring and control	Operates as quiet as 29 dBA; Network monitoring and control	'Seamless' DLP® imaging; 6-segment BrilliantColor™ color wheel; Full range of inputs, including digital (DVI-I); Filterless design; Long lamp life	7 watt sound system; Compact design and only 6.2 lb; Digital input with DVI-I port; Network monitoring and control	Widescreen, 720p; 7 Watt sound output; Digital input with HDMI port; Only 6.2 lb	Cartridge air filter; 1 Year Lamp and Filter Warranty; Digital input with DVI-I port; 7 Watt audio system; XS31: Wired LAN connection
DISPLAY TECHNOLOGY	3LCD	3LCD	1-chip DLP®	3LCD	3LCD	3LCD
PRICE (MSRP)	\$895 / \$995	\$1,195	\$1,195	\$1,295 / \$1,495	\$1,495	\$1,295 / \$1,495
BRIGHTNESS (ANSI)	2,200 / 2,600 lumens	3,000 lumens	2,600 lumens	3,000 / 3,500 lumens	2,500 lumens	2,600 / 3,100 lumens
NATIVE RESOLUTION	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	WXGA (1280x800)	XGA (1024x768)
MAX. COMPUTER INPUT	UXGA	UXGA	UXGA	UXGA	WUXGA	UXGA
MAX. VIDEO INPUT	1080i	1080i	1080p	1080i	1080p	1080i
CONTRAST RATIO	500:1	500:1	2200:1	500:1	500:1	450:1
PANEL SIZE (DIAGONAL)	0.55"	0.63"	0.55"	0.63"	0.59"	0.63"
LENS TYPE (THROW: WIDTH)	1.62-1.92:1	1.43-1.72:1	1.64-1.97:1	1.18-1.91:1	1.18-1.91:1	1.72-2.07:1
FIXED IMAGE OFFSET	Up 35%	Up 31%	Up 54.2%	Up 40%	Up 48%	Up 40%
KEystone CORRECTION	U/D 30°	U/D 30°	U/D 40°	U/D 30°	U/D 30°	U/D 20°
CLOSED CAPTION	Yes	Yes	Yes	Yes	Yes	Yes
INPUTS	Dsub15 x 2; RCA x 1 MiniStereo x 1; S-Video with included adapter; Component Video with optional adapter	Dsub15 x 2; RCA x 1 MiniStereo x 1; S-Video with included adapter; Component Video with optional adapter	DVI-I (w/HDCP) x 1; Dsub15 x 1; S-Video x 1; RCA x 1; RCA (audio) x 2; MiniStereo x 1	DVI-I (w/HDCP) x 1; Dsub15 x 1; RCA x 1; S-Video x 1; MiniStereo x 2; RCA (audio) x 2	Dsub15 x 2; HDMI (w/HDCP) x 1; S-Video x 1; RCA x 1; MiniStereo x 2; RCA (audio) x 2	DVI-I (w/HDCP) x 1; Dsub15 x 1; RCA x 1; S-Video x 1; MiniStereo x 2; RCA (audio) x 2
OUTPUTS	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1; MiniStereo x 1
SOUND SYSTEM	1 Watt; 1.1" dia. speaker x 1	1 Watt; 1.1" dia. speaker x 1	2 Watt; 1.1" dia. speaker x 1	7 Watt; 1.4" dia. speaker x 1	7 Watt; 1.4" dia. speaker x 1	7 Watt; 1.4" dia. speaker x 1
NETWORK CONTROL	Wired LAN monitor and control	Wired LAN monitor and control	—	Wired LAN monitor and control	Wired LAN monitor and control	Wired LAN - XS31 only
WARRANTY	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
LAMP LIFE	Up to 3,000 hours	Up to 4,000 hours	Up to 4,000 hours	Up to 2,500 hours	Up to 2,500 hours	Up to 3,000 hours
LAMP PART NUMBER	610 345 2456	610 345 2456	AH-62101	610 343 2069	610 343 2069	610 339 8600
FAN NOISE	As low as 29 dBA	As low as 29 dBA	As low as 29 dBA	As low as 29 dBA	As low as 29 dBA	As low as 27.5 dBA
AIR FILTER	Standard	Standard	None	Standard	Standard	Cartridge (up to 3,000 hours)
MAXIMUM PITCH	± 30° U/D	± 30° U/D	± 9° U/D	± 30° U/D	± 30° U/D	± 20° U/D
WEIGHT	5.5 lb (2.5 kg)	5.5 lb (2.5 kg)	6.4 lb (2.9 kg)	6.2 lb (2.8 kg)	6.2 lb (2.8 kg)	8.82 lb (4.0 kg)
CEILING MOUNT PN	0173-4341	0173-4341	0173-5014	0173-4338	0173-4338	0173-4327

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 ♦ Tel: 800-242-3454 ♦ E-Mail: usa@eiki.com ♦ Website: www.eiki.com

Prices and specifications are subject to change without notice. EIKI is a registered trademark of Eiki International, Inc. © 2010 Eiki International, Inc. Issued June 1, 2010


	SPECIAL PURPOSE			ULTRAPORTABLE		
	 SHORT THROW	 INTERACTIVE	DUSTPROOF	 OUR BRIGHTEST ATTACHED LENS MODELS	WIDESCREEN	
Note: Photos are not sized to scale.						
MODEL	EIP-XSP2500	LC-XIP2600	LC-XDP3500	EIP-4200 / D450	LC-XB43 / 43N	LC-WB42NA
KEY FEATURES	Short Throw, 6-segment BrilliantColor™ DLP® imaging system, long lamp life; adjustable lens shift	Interactive projector with both "pointer" and "pen" for real-time projected content annotation	"Dustproof" design with HEPA-like filter (up to 5,000 hours); Anti-smoke filter included; Wired LAN; Easy, side access to lamp and filter	'Seamless' DLP® imaging; 6-segment BrilliantColor™ color wheel; Full range of inputs, including digital (DVI-I); Filterless design; Long lamp-life. D450 is 3D Ready	Only 7.7 lb and 4500 lumens; Analog XB43 has Wired LAN connection. Analog/Digital XB43N has Wired/Wireless LAN with content delivery, and computerless slideshow	Wireless network monitoring, control and content delivery up to 802.11n; Only 7.9 lb; Computerless USB slideshow; Easy network-free wireless
DISPLAY TECHNOLOGY	1-chip DLP®	3LCD	3LCD	1-chip DLP®	3LCD	3LCD
PRICE (MSRP)	\$1,495	\$2,995	\$1,995	\$2,495 / \$2,795	\$2,745 / \$3,295	\$2,995
BRIGHTNESS (ANSI)	2,500 lumens	2,600 lumens	3,500 lumens	4,200 / 4,500 lumens	4,500 lumens	3,800 lumens
NATIVE RESOLUTION	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	WXGA (1280x800)
MAX. COMPUTER INPUT	SXGA	UXGA	UXGA	UXGA	UXGA	WUXGA
MAX. VIDEO INPUT	1080i	1080p	1080p	1080p	1080i	1080p
CONTRAST RATIO	1600:1	500:1	500:1	2500:1	1000:1	500:1
PANEL SIZE	0.55"	0.63"	0.63"	0.7"	0.8" (inorganic)	0.74"
LENS TYPE (THROW: WIDTH)	0.62:1	0.96-1.18:1	1.45-1.73:1	2.5-2.7:1	1.15-1.85:1	1.18-1.86:1
FIXED IMAGE OFFSET	Up 52-54.5%	Up 33.3%	Up 33.3%	Up 51.6%	Up 40%	Up 48%
KEystone CORRECTION	U/D 20°	U/D 30°	U/D 30°	U/D 40°	U/D 40°	U/D 40°
CLOSED CAPTION	No	Yes	Yes	Yes	Yes	Yes
INPUTS	Dsub15 x 2; S-Video x 1; RCA x 1; MiniStereo x 1	DVI-I (w/HDCP) x 1; Dsub15 x 1; 3RCA x 1; S-Video x 1; RCA x 1; MiniStereo x 2; RCA (audio) x 2	Dsub15 x 1; DVI-I (w/HDCP) x 1; S-Video x 1; RCA x 1; RCA x 3; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 1; DVI-I (w/HDCP) x 1; RCA x 1; S-Video x 1; MiniStereo x 1; RCA (audio) x 2	XB43: Dsub15 x 2; XB43N: Dsub15 x 1 and DVI-I x 1; RCA x 1 or S-Video x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 2; HDMI (HDCP) x 1; RCA x 1; S-Video x 1; MiniStereo x 2; RCA (audio) x 2; Computerless USB memory device slideshow
OUTPUTS	Dsub15 x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1
SOUND SYSTEM	2 Watt; 1.0" speaker x 1	8 Watt; 2" dia. speaker x 1	8 Watt; 2" dia. speakers x 2	10 Watt; 1.6 x 2.8" oval speakers x 2	1 Watt; 1.1" dia. speaker x 1	1 Watt; 1.1" dia. speaker x 1
NETWORK CONTROL	Wired LAN monitor and control	Wired LAN monitor and control	Wired LAN monitor and control	Wired LAN monitor and control	XB43: Wired LAN; XB43N Wired/wireless LAN with content delivery	Wired/wireless LAN monitoring, control and content delivery
WARRANTY	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
LAMP LIFE	Up to 5,000 hours	Up to 3,000 hours	Up to 3,000 hours	Up to 3,000 hours	Up to 3,000 hours	Up to 3,000 hours
LAMP PART NUMBER	23040028	23040021	23040021	AH-42001	610 333 9740	610 333 9740
FAN NOISE	As low as 34 dBA	As low as 34 dBA	As low as 33 dBA	As low as 30 dBA	As low as 31 dBA	As low as 31 dBA
AIR FILTER	None	Advanced	HEPA-like (up-to 5000 hours)	None	Standard	Standard
MAXIMUM PITCH	± 9° U/D	Up to 360°	Up to 360°	± 9° U/D	Up to 360°	Up to 360°
WEIGHT	6.6 lb (3 kg)	13.7 lb (6.2 kg)	8.2 lb (3.7 kg)	12.8 lb (5.8 kg)	7.7 lb (3.6 kg)	7.9 lb (3.6 kg)
CEILING MOUNT PN	TBA	0173-4142	0173-4142	0173-5017	0173-4305	0173-4305

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 ♦ Tel: 800-242-3454 ♦ E-Mail: usa@eiki.com ♦ Website: www.eiki.com

Prices and specifications are subject to change without notice. EIKI is a registered trademark of Eiki International, Inc. © 2010 Eiki International, Inc. Issued June 1, 2010

STANDARD RESOLUTION - XGA

	CONFERENCE			AUDITORIUM		POWERHOUSE	THEATER
Note: Photos are not sized to scale.							
MODEL	LC-XL100 / LC-XL200	LC-XGC500	EIP-5000	LC-X85	LC-X800	LC-XT5	
KEY FEATURES	Durable inorganic imaging engine; 13,000 hour filter life; 7 Watt stereo output; Mechanical shutter; High brightness and contrast; Low cost for great features	Cartridge air filter; Automatic lamp changer and failsafe; dependability in mission-critical situations and hard-to-reach installations	1 DLP® imaging engine; Projector Stack and VideoWall features; Filterless design; 2 lamps	Highest brightness portable; 3LCD+One technology for superior color reproduction; Cartridge air filter	Our brightest projector to run on standard 110V, 15 amp circuit; Cartridge air filter; 4000:1 contrast ratios; Interchangeable input modules; 2 lamps	Our brightest at 15,000 lumens; Up to 600" image diagonal; Interchangeable input modules; 4 lamps; Accepts inputs up to 1080p	
DISPLAY TECHNOLOGY	3LCD	3LCD	1-chip DLP®	3LCD+One	3LCD+One	3LCD	
PRICE (MSRP)	\$4,295 / \$5,295	\$6,995	\$7,495	\$9,995	\$19,995	\$29,995	
BRIGHTNESS (ANSI)	5,000 / 6,000 lumens	5,000 lumens	5,200 lumens	7,000 lumens	12,000 lumens	15,000 lumens	
NATIVE RESOLUTION	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	
MAX. COMPUTER INPUT	UXGA	SXGA+	UXGA	UXGA	UXGA	UXGA	
MAX. VIDEO INPUT	1080p	1080i	1080i	1080p	1080p	1080p	
CONTRAST RATIO	1000:1	1100:1	1200:1	2200:1	4000:1	2000:1	
PANEL SIZE	0.8" (inorganic)	1.0"	0.7"	1.3" (inorganic)	1.8" (inorganic)	1.8" (inorganic)	
LENS TYPE (THROW: WIDTH)	1.70-2.89:1	1.64-2.14:1	1.81-2.20:1	Supplied without lens	Supplied without lens	Supplied without lens	
POWER LENS SHIFT	U/D 50%; L/R 10%	Up 50%; L/R 15%	Up 50%; L/R 15%	Up 50%; L/R 10%	U/D 50%; L/R 10%	U/D 50%; L/R 10%	
KEystone CORRECTION	U/D 40°; L/R 20°	U/D 40°; L/R 20°	U/D 30°; L/R 30°	U/D 40°; L/R 20°	U/D 40°; L/R 20°	U/D 40°; L/R 20°	
INPUTS	Dsub15 x 1; DVI-D (w/HDCP) x 1; BNC x 5; S-Video x 1; RCA x 1; MiniStereo x 2; RCA (audio) x 2	Dsub15 x 1 or DVI-D (w/HDCP) x 1; BNC x 5 or BNC x 3; RCA x 1 or S-Video x 1 with RCA (audio) x 2; MiniStereo x 1	Dsub15 x 1; BNC x 5 or BNC x 3; DVI-D (w/HDCP) x 1; RCA x 1; S-Video x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 1 or DVI-D (w/HDCP) x 1; BNC x 5 or BNC x 3; RCA x 1 or RCA x 3 or S-Video x 1; MiniStereo x 2	Dsub15 x 1 or DVI-D (w/HDCP); BNC x 5 or BNC x 3 or BNC x 1 or S-Video x 1; Empty module bay x 2	Dsub15 x 1, DVI-D (w/HDCP) x 1; BNC x 5; S-Video x 1; Empty module bay x 2; (Requires 240 V/60 Hz power)	
OUTPUTS	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	—	—	
SOUND SYSTEM	7 Watt; 1.46" speaker x 1	3 Watt; 2.0" x 3.5" oval speakers x 2	3 Watt; 1.3" dia. speakers x 2	—	—	—	
NETWORK CONTROL	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control and system management with optional module	
WARRANTY	3 years	3 years	3 years	3 years	3 years	3 years	
LAMP LIFE	Up to 3,000 hours	Up to 3,000 hours per lamp	Up to 2,500 hours per lamp	Up to 3,000 hours	Up to 3,000 hours per lamp	Up to 3,000 hours per lamp	
LAMP PART NUMBER	610 347 5158 / 610 346 9607	610 342 2626 (2)	AH-50001 (1) & AH-50002 (1)	610 341 1941	610 341 9497 (2)	610 334 6267 (4)	
FAN NOISE	As low as 31 dBA	As low as 32 dBA	As low as 35 dBA	As low as 35 dBA	As low as 42 dBA	As low as 51 dBA	
AIR FILTER	Cartridge (13,000 hours)	Cartridge (10,000 hours)	None	Cartridge (10,000 hours)	Cartridge (10,000 hours)	Standard	
MAXIMUM PITCH	Up to 360°	Up to 360°	± 9° U/D	Up to 360°	Up to 360°	± 10° U/D	
WEIGHT	22.3 lb (9.7 kg)	34 lb (15.4 kg)	33.2 lb (15.1 kg)	25.1 lb (11.4 kg)	60.85 lb (27.6 kg)	80.5 lb (36.5 kg)	
CEILING MOUNT PN	0173-4343	0173-4304	0173-5002	0173-4313	0173-4325	0173-4222	

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 ♦ Tel: 800-242-3454 ♦ E-Mail: usa@eiki.com ♦ Website: www.eiki.com

Prices and specifications are subject to change without notice. EIKI is a registered trademark of Eiki International, Inc. © 2010 Eiki International, Inc. Issued June 1, 2010

HIGH-RESOLUTION AND WIDESCREEN

	720p/WXGA (1280x800)			SXGA+ (1400x1050)		HD 1080p
Note: Photos are not sized to scale.						
MODEL	LC-WGC500A	EIP-WX5000	LC-W5	LC-SXG400	EIP-SXG20	EIP-HDT20
KEY FEATURES	High-brightness widescreen (1280x800); Cartridge air filter; Automatic lamp changer and failsafe; 3000:1 contrast ratio; Picture in Picture; Picture by Picture features	High-brightness widescreen (1280x800); Advanced 3-Chip DLP® engine; Projector Stack and VideoWall features	Widescreen (1366x800); Cartridge air filter; High brightness and contrast; Interchangeable input modules	High Resolution SXGA+ (1400x1050); Push button lens changer; 4,200 lumens; Cost-effective	SXGA+ (1400x1050); Cartridge air filter (up to 35,000 hours); High brightness at 7,500 lumens; Interchangeable input modules; DICOM compatibility	1080p (1920x1080); 1DLP® image engine; interchangeable color wheels to maximize brightness or color saturation; Cartridge air filter; Interchangeable input modules
DISPLAY TECHNOLOGY	3LCD	3-chip DLP®	3LCD	3LCD	1-chip DLP®	1-chip DLP®
PRICE (MSRP)	\$6,995	\$13,995	\$14,995	\$6,995	\$14,995	\$21,995
BRIGHTNESS (ANSI)	5,000 lumens	5,200 lumens	6,000 lumens	4,200 lumens	7,500 lumens	6,500 lumens
NATIVE RESOLUTION	WXGA (1280x800)	WXGA (1280x800)	WXGA (1366x800)	SXGA+ (1400x1050)	SXGA+ (1400x1050)	1080p (1920x1080)
MAX. COMPUTER INPUT	WUXGA	WXGA	WXGA	UXGA	UXGA	WUXGA
MAX. VIDEO INPUT	1080p	1080p	1080p	1080i	1080p	1080p
CONTRAST RATIO	3000:1	1800:1	2000:1	1300:1	7500:1	7500:1
PANEL SIZE	0.95" (inorganic)	0.65"	1.22" (inorganic)	1.0"	0.95"	0.95"
LENS TYPE (THROW: WIDTH)	1.61-2.10:1	1.80-2.25:1	Supplied without lens	1.69-2.20:1	Supplied without lens	Supplied without lens
POWER LENS SHIFT	Up 50%; L/R 15%	U/D 66%; L/R 35%	U/D 88%; L/R 13%	Up 50%; L/R 15%	U/D 55%; L/R 45%	U/D 67%; L/R 41.5%
KEystone CORRECTION	U/D 40°; L/R 20°	U/D 40°; L/R 30°	U/D 40°; L/R 20°	U/D 40°	U/D 30°; L/R 30°	U/D 30°; L/R 30°
INPUTS	HDMI (w/HDCP) x 1 or Dsub15 x 1; BNC x 5 or BNC x 3; S-Video x 1; RCA x 1; MiniStereo x 1; RCA (audio) x 2	HDMI x 1; DVI-D (w/HDCP) x 1; Dsub15 x 1; BNC x 5; S-Video x 1; RCA x 1; MiniStereo x 1	HD15 x or DVI-D (w/HDCP) x 1; BNC x 5 or BNC x 3 or BNC x 1 or S-Video x 1; Empty module bays x 2	Dsub15 x 1 or DVI-D (w/HDCP) x 1; BNC x 5 or BNC x 3; S-Video x 1; RCA x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 1; DVI-D x 1; HDMI (w/HDCP) x 1; BNC x 5; S-Video x 1; Empty module bay x 1	HDMI (w/HDCP) x 1; DVI-D x 1; Dsub15 x 1; BNC x 5; S-Video x 1
OUTPUTS	Dsub15 x 1 MiniStereo x 1	Dsub15 x 1 MiniStereo x 1	—	Dsub15 x 1 MiniStereo x 1	Dsub15 x 1	Dsub15 x 1
SOUND SYSTEM	3 Watt; 2.0" x 3.5" oval speakers x 2	3 Watt; 1.3" x 2.6" oval speakers x 2	—	1 Watt; 1.1" dia. speaker x 1	—	—
NETWORK CONTROL	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control and system management with optional module	Wired LAN monitor & control	Wired LAN monitor & control
WARRANTY	3 years	3 years	3 years	3 years	3 years	3 years
LAMP LIFE	Up to 3,000 hours per lamp	Up to 3,000 hours per lamp	Up to 3,000 hours per lamp	Up to 3,000 hours	Up to 2,500 hours per lamp	Up to 2,500 hours per lamp
LAMP PART NUMBER	610 342 2626 (2)	AH-55001 (2)	610 337 0262 (2)	610 335 8093	610 343 5336 (2)	610 343 5336 (2)
FAN NOISE	As low as 31 dBA	As low as 34 dBA	As low as 50 dBA	As low as 35 dBA	As low as 36 dBA	As low as 36 dBA
AIR FILTER	Cartridge (10,000 hours)	Standard	Cartridge (10,000 hours)	Standard	Cartridge (up to 35,000 hours)	Cartridge (up to 35,000 hours)
MAXIMUM PITCH	Up to 360°	± 9° U/D	Up to 360°	Up to 360°	Up to 360°	Up to 360°
WEIGHT	34 lb (15.4 kg)	58.4 lb (26.5 kg)	60.85 lb (27.6 kg)	19.62 lb (8.9 kg)	44.1 lb (20 kg)	44.1 lb (20 kg)
CEILING MOUNT PN	0173-4304	0173-5015	0173-4325	0173-4304	0173-5016	0173-5016

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 ♦ Tel: 800-242-3454 ♦ E-Mail: usa@eiki.com ♦ Website: www.eiki.com

Prices and specifications are subject to change without notice. EIKI is a registered trademark of Eiki International, Inc. © 2010 Eiki International, Inc. Issued June 1, 2010